



An unparalleled 16" of ground clearance (double that of most SUVs). An awe-inspiring 430-lb.-ft. of torque. A unique Central Tire Inflation System that enables you to

adjust tire pressure without stopping to adapt to varied terrain. TorqTrac 4 technology that monitors all four wheels and automatically stops tire spin by locking the differential and redistributing power to the wheels that have traction. All of which means you can go places and do things no other wheeled vehicle in the world can. For a free video or brochure, or to contact your closest dealer for a test drive,

call 1-800-732-5493. [www.hummer.com](http://www.hummer.com)

# THE WORLD. UNABRIDGED.

**HUMMER**



## SPECIFICATIONS AND PERFORMANCE DATA

	2-Door Hard Top		4-Door Hard Top		4-Door Open Top		4-Door Wagon	
	Standard	Metric	Standard	Metric	Standard	Metric	Standard	Metric
<b>Curb Weight (Note 1):</b>								
Turbo Diesel: 10,300 / 10,800 lb. GVWR	6,500 lbs.	2,948 kg	6,900 lbs.	3,130 kg	6,750 lbs.	3,061 kg	7,090 lbs.	3,216 kg
<b>Payload (Notes 1 &amp; 2):</b>								
Turbo Diesel: 10,300 lb. GVWR	3,800 lbs.	1,724 kg	3,400 lbs.	1,542 kg	3,550 lbs.	1,610 kg	3,210 lbs.	1,456 kg
10,800 lb. GVWR	4,300 lbs.	1,950 kg	3,900 lbs.	1,769 kg	NA	NA	3,710 lbs.	1,683 kg
<b>Gross Axle Weight Rating:</b>								
Front: 10,300 / 10,800 lb. GVWR	4,100 lbs.	1,860 kg	4,100 lbs.	1,860 kg	4,100 lbs.	1,860 kg	4,100 lbs.	1,860 kg
Rear: 10,300 / 10,800 lb. GVWR	6,800 lbs.	3,084 kg	6,800 lbs.	3,084 kg	6,800 lbs.	3,084 kg	6,800 lbs.	3,084 kg
<b>Maximum Towed Load (Note 3):</b>								
Turbo Diesel: 10,300 / 10,800 lb. GVWR	8,300 lbs.	3,765 kg	7,900 lbs.	3,583 kg	8,050 lbs.	3,651 kg	7,710 lbs.	3,497 kg
<b>Length (Note 1):</b>	184.5 in.	4,686 mm	184.5 in.	4,686 mm	184.5 in.	4,686 mm	184.5 in.	4,686 mm
<b>Maximum Height:</b>	75 in.	1,905 mm	75 in.	1,905 mm	77 in.	1,956 mm	75 in.	1,905 mm
<b>Width (Without Mirror):</b>	86.5 in.	2,197 mm	86.5 in.	2,197 mm	86.5 in.	2,197 mm	86.5 in.	2,197 mm
<b>Wheelbase:</b>	130 in.	3,302 mm	130 in.	3,302 mm	130 in.	3,302 mm	130 in.	3,302 mm
<b>Ground Clearance:</b>	16 in.	406 mm	16 in.	406 mm	16 in.	406 mm	16 in.	406 mm
<b>Track Width:</b>	71.6 in.	1,819 mm	71.6 in.	1,819 mm	71.6 in.	1,819 mm	71.6 in.	1,819 mm
<b>Grade Capability:</b>	60%	60%	60%	60%	60%	60%	60%	60%
<b>Side-Slope Capability:</b>	40%	40%	40%	40%	40%	40%	40%	40%
<b>Approach Angle Without Winch:</b>	72°	72°	72°	72°	72°	72°	72°	72°
<b>Approach Angle With Winch:</b>	47°	47°	47°	47°	47°	47°	47°	47°
<b>Departure Angle:</b>	37.5°	37.5°	37.5°	37.5°	37.5°	37.5°	37.5°	37.5°
<b>Runflat Capability (Note 4):</b>								
(At 30 mph)	20 miles	32.2 km	20 miles	32.2 km	20 miles	32.2 km	20 miles	32.2 km
<b>Turning Radius:</b>	26.5 ft.	8.1 m	26.5 ft.	8.1 m	26.5 ft.	8.1 m	26.5 ft.	8.1 m

## COMPONENTS AND FEATURES

### Turbo Diesel Engine :

Type : V8, 6.5L Diesel Turbocharged, Electronically Controlled\*  
**Horsepower** : (@ 3,400 rpm): 195 hp (145 kW)  
**Torque** : (@ 1,800 rpm): 430 lb.-ft. (583 Nm)  
**Governor Type** : Electronic  
**Displacement** : 396 cu. in. (6.5L)  
**Bore and Stroke** : 4.06 x 3.82 in. (10.3 x 9.7 cm)  
**Compression Ratio** : 20.2:1

**Maximum Speed** : 83 mph (134 kph)

**Typical Accel.** : (0 to 60 mph) 18.0 sec.

**Fording Depth** : 30 in. (76.2 cm)

**Fuel Capacity** : 25 gal. (95L). Plus 17 gal. (64L) res.

**Transmission** : 4L80-E 4-speed automatic

**Gear Ratios** : 1st - 2.48:1, 2nd - 1.48:1,

3rd - 1.00:1, 4th - 0.75:1, Reverse - 2.08:1,

Torque Converter Ratio - 2.2:1

**Transfer Case** : New Venture Gear Model 242.

**Gear Ratios** : Low 2.72:1, High 1:1

**Axles** : Hypoid with a ratio of 2.56:1 Continuous torque rating is 1,424 lb.-ft.

**Geared Hubs** : Gear Ratio - 1.92:1.

**Frame** : Steel Box section with 5 crossmembers

**Electrical** : 12 Volt 124 Amp - Alternator

**Steering** : Power assisted with a variable ratio of 13/16:1

**Differential** : Zexel Torsen® II torque biasing differential

**Brakes** : Hydraulic actuated, four-wheel inboard mounted Meritor-WABCO ABS power disc brakes with translucent reservoir and level sensor. Rotors are 10.5 in. (266 mm) in diameter with an effective area of 17.4 sq. in. (112 sq. cm) each. Parking brake manually activates rear service brakes.

**Suspension** : Independent double A-frame with open-end coil springs and hydraulic shock absorbers

**Tires** : 37 x 12.50R-16.5 LT load range "D" Goodyear Wrangler MT radial

## VEHICLE MODELS

## STANDARD EQUIPMENT

## OPTIONAL EQUIPMENT



4-Door Open Top



2-Door Hard Top



4-Door Hard Top



4-Door Wagon

- 4-Speed Automatic Transmission
- 4-Wheel ABS Power Disc Brakes
- Translucent Brake Fluid Reservoir w/Level Sensor
- Auxiliary Fuel Tank
- Tachometer
- MT Tread Tires
- Utility Lighting Package
- Heat and Sound Insulation
- Halogen Headlights
- Aluminum Body
- Tonneau Cover (4-Passenger Models)
- 124 Amp Alternator
- Vertical Rear Doors (Wagon Model)
- Serpentine Drive Belt
- Flow-Through Ventilation

- Full-Time 4WD System
- Power Steering
- High-Back Bucket Seats
- 3-Point Seat Belts
- Padded Interior
- Power Door Locks (Including Wagon Rear Door)
- AM/FM Stereo w/cassette
- Glove Box
- Geared Hubs
- EZ-Kool® Glass
- Driver and Front Passenger Seat Armrest
- Sliding Rear Window (2-Door and 4-Door Models)
- Power Windows
- Air Conditioning with Auxiliary Rear Unit
- TorqTrac 4™ (TT4)

- Central Tire Inflation System
- Trailer Towing System
- Driveline Protection
- Runflat Tire System
- Highway Touring Tires
- Tire Bead Lock System
- Black Vinyl Seats
- Power Mirrors
- Remote Keyless Entry
- Rocker Panel Protection
- Heated Windshield

- Deluxe Rearview Mirror
- Rear Window Defroster (2-Door and 4-Door Models)
- Monsoon™ Premium Audio System w/CD Player/Changer
- Brush Guard
- 12,000 lb. Winch
- Body-Colored Wheels
- 10,800 lb. GVW

## COLORS

Candy Apple • Night Storm • Mesa Dusk  
 Black • Competition Yellow  
 Silver Metallic • White • Bright White

Notes: 1) The data on this page applies to models without winch and optional accessories. Models with winch are impacted as follows: Payload: Reduce by 137 lbs. (62 kg); Curb Weight: Increase by 137 lbs. (62 kg); Length: Increase by 6 in. (152.4 mm). 2) Payload includes passengers, optional equipment, and trailer tongue weight. 3) Gross Combination Weight (GCW) of vehicle and trailer cannot exceed 14,800 lbs. (6,719 kg) for highway use only. A weight-carrying hitch gives your vehicle the capability to tow a maximum weight of 5,000 lbs. (2,270 kg). A weight-distributing hitch with spring bars gives your vehicle the capability to tow a maximum weight of up to 8,300 lbs. (3,765 kg). These are not necessarily weights the vehicle will tow at sustained highway speeds or varying altitudes. NOTE: The maximum allowable weight your vehicle can tow off-road, no matter what type of hitch is being used, is 5,000 lbs. (2,270 kg). 4) Optional, for emergency use only, a "get home" capability which will cause tire damage. Consult your local Hummer dealer for availability of accessories and current specifications. All specifications are based on latest information available at time of printing. Pictured vehicles may vary from actual production models. Manufacturer reserves the right to change prices, colors, materials, equipment, and specifications at any time and without prior notice. Details and specifications may vary according to local regulations and conditions. Some models may not be available at all times in all markets. See dealer for 3-year/36,000-mile warranty details. Copyright AM General, 1998. HUMMER®, HUMVEE®, TorqTrac 4™ (TT4), Hummer Genuine™ Accessories and the vehicle's grille design are registered trademarks of AM General Corporation.

# HUMMER®